

TEXPRINT HR 105 G/M²

PROPERTIES	
Article number	SX30HR
Weight transfer paper	105 g/m²
Available sheet size	A4, A4+, A3, A3+
Available roll width	33 cm, 43 cm, 61 cm, 111 cm, 137 cm, 162 cm, 257 cm
Available roll length	34 m, 84 m, 92 m, 120 m
Dye sub coating type	Semi-porous coating
Suitable for segment	Metal, aluminium or ceramics, Textile, Textile non-porous
Drying properties	High speed drying
Core	3"
Printing side	Outside

USP's

- Very fast drying
- Superb stability against wet cockling
- Semi-porous coating reduces outgassing
- Available in DIN sheets sizes
- Available in rolls for Epson (<15 cm diameter)
- Suitable for metal and ceramics

TexPrint HR SX

SX30HR 105 g/m²





Notice: TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

.....

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.











