

BRAGA 370

PROPERTIES

Article number	FI/654-XX-00
Textile application	Curtains
Abrasion resistance	> 45.000
Available roll width	140 cm, 280 cm
Available roll length	25 m
Base material	61% PES, 23% AC, 3% VI, 13% TIO2
Core	3"
Flame retardant	No
Reach	Yes
OEKO-TEX® Certified	Yes
Printing side	Indicated side
PVC free	Yes
Structure	Woven with coating
Sublimation settings	195°C – ± 45 seconds
Weight textile	370 gsm

USP's

- Water repellent
- Non fraying / cold cutting
- Block-out with white backside
- High abrasion resistance (Martindale tested)
- PVC free



Notice: TTS' products must be tested to determine the suitability of the product in combination with your equipment and methods of use. TTS maximum obligation shall be to replace any product supplied by TTS, which has been proven to be defective. TTS is not liable for any injury, direct or consequential, arising from the use of, or the inability to use our products.

The above mentioned data are according to the latest state and are non-binding. For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications.

Texo Trade Services | Oostbaan 601 | 2841 ML Moordrecht | The Netherlands
T +31 182 62 39 44 | E sales@texo-trade.com | W texo-trade.com

